


(12) UK Patent Application (19) GB (11) 2 122 337 A

(21) Application No 8313558
 (22) Date of filing 17 May 1983
 (30) Priority data
 (31) 8214384
 (32) 18 May 1982
 (33) United Kingdom (GB)
 (43) Application published
 11 Jan 1984
 (51) INT CL³
 G01K 11/00
 G01N 21/49
 (52) Domestic classification
 G1A A3 A7 C1 C8 D4 DM
 G5 G7 P10 P12 P17 P18 P1
 P6 R6 R7 S10 S12 S4 T14
 T22 T5
 H4D 72X 749 751 759 769
 773 781 782 783
 U1S 2166 G1A H4D
 (56) Documents cited
 GB A 2091874
 GB A 2037448
 GB A 2033078
 GB 1587768
 GB 1576797
 GB 1560124
 GB 1538316

(58) Field of search
 G1A
 H4D
 (71) Applicants
 National Research
 Development
 Corporation
 (United Kingdom),
 101 Newington
 Causeway,
 London SE1 6BU.
 (72) Inventors
 Arthur Harold Hartog,
 David Neil Payne.
 (74) Agent and/or Address for
 Service
 C. Hasler,
 Patents Department,
 National Research
 Development
 Corporation,
 101 Newington
 Causeway,
 London SE1 6BU.



(54) Fibre optic sensing device

(57) A detector comprises a pulsed optical radiation source (10) and a length of optic fibre (18) sensitive to local variations in a physical variable e.g. temperature. Changes in radiation back-scattered by the fibre are received by a detector (24) which gives an output dependent on local changes in the physical variable, and preferably in the form of a plot of variable against distance. The fibre may have a liquid core, and several fibres with individual laser sources may be multiplexed to a common detector.



GB 2 122 337 A

2122337



2122337

2/4




Fig. 3




Fig. 4

2122337

3/4




Fig. 5

2122337

4/4




Fig. 6

SPECIFICATION

Fibre optic sensing device

- 5 This invention relates to a sensing system in which the sensor is an optical fibre. 5
 Usually the fibre will be a temperature sensor, but other variables such as pressure or stress may also be sensed.
- Several forms of temperature sensors based on optical fibres are already known. In Applied Optics, Vol. 20, No. 19 1st October 1981, pages 3408 to 3414, M. Gottlieb and G.B. Brandt describe a fibre optic
 10 temperature sensor in which thermally generated black-body radiation produced by a hot spot within the 10
 core of the fibre itself is sensed. In the same journal and volume, No. 22, 15th November 1981, pages 3867 to 3873, the same authors describe an optical fibre temperature sensor in which transmission intensity effects are sensed; the device relies on loss effects in the cladding and jacket of the fibre.
- A disadvantage of both prior art arrangements is that temperature can be sensed only at one position, at
 15 which the maximum temperature occurs, and that that position is unknown. 15
 In the present invention the variable at any position along the fibre can be sensed, and related to the position, i.e. a distributed sensor is provided.
- According to the invention, there is provided a detector apparatus including a fibre optic sensor comprising a length of optical fibre having a parameter which varies in accordance with a physical variable
 20 to be sensed, optical pulse supply means for supplying to said length of optical fibre a pulse of 20
 electromagnetic radiation at visible, ultraviolet or infrared wavelengths, radiation sensing means positioned to receive optical radiation back-scattered by the length of optical fibre and detector means responsive to said radiation sensing means to provide an output signal dependent on the intensity of the back-scattered radiation.
- 25 Usually, but not essentially, the variable to be sensed is temperature. The parameter of the fibre which 25
 varies locally in accordance with the variable may be an optical parameter such as the Rayleigh scattering coefficient or the refractive index of the fibre core or the refractive index of the fibre cladding or the absorption loss of the fibre.
- In its simplest form the apparatus comprises a pulsed laser to supply pulses of radiation; a beam splitter
 30 through which pulses are transmitted to a coupling lens, and an index-matching cell through which pulses 30
 are coupled to the length of optical fibre; a further lens to focus light back-scattered by the fibre and reflected by the beam splitter; an optical receiver to receive the focused, back-scattered light; and an electronic processor to supply an output signal in convenient form.
- In a preferred form said length of optical fibre is a length of liquid-core optical fibre, which is preferably
 35 coupled to the pulse supply means and the light sensing means through a length of solid core optical fibre. 35
 Also according to the invention, there is provided a method of sensing the local value of a physical variable comprises providing a length of optical fibre having a parameter which responds to said physical variable, supplying to the fibre an optical pulse of radiation and sensing the variation of radiation back-scattered by said fibre. The method can be regarded as optical time domain reflectometry.
- 40 The invention will now be described by way of example only with reference to the accompanying 40
 drawings in which:-
- Figure 1* illustrates schematically a basic distributed fibre optic temperature sensor according to the invention;
Figure 2 illustrates typical back-scattered signals related to a local variable;
 45 *Figure 3* illustrates the variation of power ratio with temperature difference; 45
Figure 4 illustrates schematically a preferred form of the sensor; and
Figures 5 and 6 illustrate two alternative arrangements of a multiple distributed fibre optic temperature sensor.
- In *Figure 1*, light from a pulsed laser 10 passes through a 50% beam splitter 12 and is focused by a lens 14
 50 onto the end 16 of a length of test fibre 18. Optionally the end 16 is immersed in a cell 20 (shown dotted) of 50
 index matching liquid so that Fresnel reflection from the air-fibre interface is eliminated.
- Any light back-reflected by the fibre 18 passes through the lens 14 and is reflected by the beam splitter 12 to be focused by a further lens 22 onto an optical receiver 24 connected to a microprocessor 26.
- When an optical pulse from the laser 10 passes along the fibre, it is attenuated by several mechanisms,
 55 one of which is Rayleigh scattering. A portion of the optical power is continuously scattered in all directions 55
 and some of the scattered light is guided back towards the source and reaches the optical receiver 24. If the scattering and certain other fibre parameters are constant along the length of the fibre, the receiver 24 receives a signal which decays exponentially with time. Such an arrangement has previously been used to test the quality of optical fibres.
- 60 Suppose however that the test fibre 18 is of a construction such that the back-scattering is dependent on 60
 temperature, and that a length of the fibre is at a different temperature from the preceding and succeeding fibre lengths. The variation with time of the back-scattered radiation would then show a difference in intensity during the time interval in which light scattered in that length of fibre is received. Typical received signals are illustrated in *Figure 2* in which the back-scattered signals are plotted against time T
 65 corresponding to distance D of the scattering length from the end 16 of the fibre. A central section of the fibre 65

18 about 15 metres long is heated to three temperatures above and cooled to one temperature below an ambient temperature of 20°C, and typical corresponding back-scatter signals are illustrated. The magnitude of the step-change in intensity clearly indicates the temperature difference, and the times the step-changes are received indicate the positions of the temperature changes.

5 Let the power returning from a point at distance z from the end 16 of the fibre be $P(z)$. It has been shown for the fibre-quality measurements using back-scatter sensing referred to above that:-

$$10 \quad P(z) = \frac{1}{2} P_0 W S \alpha_s v_g \exp - \int_0^z (\alpha_f(x) + \alpha_b(x)) dx \quad (1) \quad 10$$

where

P_0 = power launched

W = pulse width

α_s = attenuation coefficient due to Rayleigh scattering

15 $\alpha_f(x)$ and $\alpha_b(x)$ = attenuation coefficients in forward and reverse directions, as functions of position x in the fibre 15

$$20 \quad v_g = \frac{C}{N_1} = \frac{C}{(n_1 - \lambda) \frac{dn_1}{d\lambda}} \quad 20$$

is the group velocity in the fibre (C is the speed of light in vacuo, n_1 the refractive index of the core, and λ the operating wavelength).

25 Here S is the back-scatter factor which, for step-index multimode fibres, may be expressed as:- 25

$$S = \frac{3}{8} \frac{(NA)^2}{n_1^2} = \frac{3}{8} \frac{(n_1^2 - n_2^2)}{n_1^2} \quad (2) \quad 30$$

30 where n_1 and n_2 are the refractive indices of the core and cladding, respectively, and $NA = (n_1^2 - n_2^2)^{1/2}$ is the numerical aperture of the fibre.

From equation (1) it can be seen that if the quantities S , α_s , n_1 and $(\alpha_f + \alpha_b)$ are invariant with fibre length, the back-scattered signal decays exponentially, as explained above. It has now been realised that if one or 35 more of the parameters varies strongly with temperature or another variable in a known way, then the back-scatter curve, as illustrated in Figure 2, can be used to determine a change in the variable which locally affects the fibre, and also the position of the change along the fibre. A typical variation of power ratio PR in decibels against temperature difference ΔT in °C is shown in Figure 3.

The distance resolution of the sensor is limited by the pulse width of the laser, the frequency response of 40 the receiver, and the dispersion (pulse distortion) of the fibre. Typically the pulse duration is between 1 and 300 nanoseconds.

Clearly, the more the parameter varies with, e.g. temperature, the higher the resolution of the sensor. While most optical fibres have some temperature variation in at least one of the parameters, fibre construction can be selected to maximise the variations. For example, liquids have relatively high 45 temperature dependence of refractive index n , and Rayleigh scatter coefficient α_s . From equation (1) it can be seen that the power back-scattered by the fibre is directly proportional to both the scattering coefficient α_s , so that a preferred embodiment of the present invention uses a liquid core optical fibre.

Liquid core optical fibres have been known for sometime, see Electronics Letters 27th July 1972, Vol. 8 No. 15 pages 374 to 376, and Opto-electronics, 5, 1973, pages 297 to 307, in which papers Payne and Gambling 50 describe the preparation and properties of liquid core optical fibres.

One embodiment of a distributed temperature sensor using a liquid core optical fibre is illustrated in Figure 4. The pulsed laser 10, beam splitter 12, lenses 14 and 22, and index matching cell 20 are arranged as in Figure 1. The lens 14 now focuses light onto a launch fibre 30 of conventional solid construction, the fibre 30 passing through a cladding-mole stripper 28 and into one end of a liquid core optical fibre 32. The ends of 55 the fibres 30 and 32 are enclosed by a sealed joint 34 filled with the same liquid as the liquid core fibre 32. The other end of the fibre 32 is connected to a liquid-containing expansion chamber 36 sealed by a flexible diaphragm 38 to retain an inert gas in the space 40 over the liquid free surface.

Back-scattered light is reflected by the beam splitter 12 through the lens 22 onto a silicon avalanche photodetector 42 connected to a transimpedance amplifier 44. The output of amplifier 44 passes through a 60 transient digitiser 46 to a digital processor 48 which supplies a display unit 50. The processor 48 is also connected to the laser 10.

Conveniently, the laser 10 is a semiconductor laser operating in the 0.85 to 0.91 micrometre region. The pulse width is chosen depending on the distance resolution required; a pulse width of 10 nanoseconds will give a resolution of about 1 metre.

65 The lens 14 focuses the pulsed laser beam onto the end face of the launch fibre. To minimise Fresnel 65

reflection so as to avoid saturating the photodetector 42, the index matching cell 20 is arranged to have an angled receiving face adjacent the lens 14. Alternatively, a polariser P and analyser A are placed, as indicated by the broken lines, between the laser 10 and the beam splitter 12 and between the beam splitter 12 and the lens 22 respectively.

5 The launch fibre 30 carries the input pulses with low loss to the measurement zone, and is conveniently coupled to the liquid core optical fibre 32 by inserting a few centimetres of launch fibre into the liquid core and surrounding the joint with the core liquid in the sealed joint 34; clearly the launch fibre external diameter is preferably just less than the internal diameter of the core. To reduce coupling losses in the back-scattered light the core/cladding diameter ratio should be as large as is allowed by consideration of propagation loss in the launch fibre; for example a core-to-cladding diameter ratio of 1:1.4 will produce coupling losses of only 10 3dB (optical) and insignificant propagation loss.

The launch fibre has the second function of limiting the range of angles at which back-scattered light is accepted from the liquid core fibre. The numerical aperture of the launch fibre 30 is arranged to be less than the numerical aperture at any point, including the hottest point, of the liquid core fibre 32. The reason is that, 15 as the temperature of the liquid core fibre increases, as explained above, the major effects are that the scattering loss coefficient α_s increases and the refractive index n_1 decreases, causing the numerical aperture to decrease. In equation (1), these effects act in opposition on the power reaching the photodetector, so the effect of a change in numerical aperture must be eliminated. By arranging the launch fibre to place a limit on the numerical aperture of the device, i.e. to act as a mode filter, the arrangement is made largely insensitive 20 to any change in numerical aperture of the liquid core fibre.

Alternatively, an angular stop (not illustrated) may be placed close to the lens 14 so as to limit the angular range of light rays which are allowed to pass to the photodetector 42.

A further temperature-dependent effect can be observed. The temperature changes along the fibre causes a longitudinal change in refractive index of the core, which causes ray bending at the interface between fibre 25 lengths at different temperatures. The direction of bending is such that scattered rays are accepted by the mode filter which originally travelled at angles which would be rejected by the filter, leading to an error, but the effect is small compared with the temperature variation of the Rayleigh scattering coefficient α_s and adds to the latter effect.

The highest temperature to which the liquid core fibre can be exposed, other than the limitation of the liquid boiling point, is that at which temperature coefficient of refractive index of the liquid causes the 30 numerical aperture of the liquid core fibre to decrease to that of the launch fibre. The lowest usable temperature is close to the liquid freezing point.

The silicon avalanche photodetector 42 has an operating wavelength shorter than 1.1 micrometres and therefore the operating wavelength should be in this range. The transimpedance amplifier 44 has a low input 35 impedance and has sufficient bandwidth to amplify pulses of similar width to the laser pulses without significant distortion, and should have a noise figure or input-equivalent noise power as low as possible to avoid signal degradation.

The transient digitiser 46 is controlled by the digital processor 48, and samples the back-scattered signal from each laser pulse at times corresponding to any point of interest along the fibre. All samples are 40 preferably obtained from a single laser pulse, so fluctuations of laser output power do not affect the measurement. Any convenient method of measurement may be used, such as boxcar integration and averaging, single point analogue-to-digital conversion etc.

The processor 48 controls the operation of the laser 10 and the digitiser 46, averages sets of readings provided by the digitiser 46 to improve the signal-to-noise ratio, and processes the averaged back-scatter 45 waveform, according to an algorithm depending on the nature of the temperature-sensitive parameter, and provides a suitable signal to the display unit 50.

The length of the liquid core sensing fibre is limited by the attenuation of the fibre and the pulse dispersion, but the use of a low dispersion launch fibre, e.g. a graded index fibre, allows the detection equipment to be at a position remote from the liquid core temperature sensing fibre, e.g. at a distance of 50 several kilometres.

Figure 4 illustrates a single distributed fibre optic temperature sensor. In practice, it is expected that multiple fibre sensors will be used, and such sensors may be multiplexed.

A first embodiment of a time-division multiplexed sensor is shown schematically in Figure 5. An array of lasers 52A, 52C.....52N are each connected by an respective solid core input optical fibre 54A, 54C.....54N 55 to one part of an array of four-port couplers 56A, 56C56N. Two further ports of each coupler 56 are connected through respective solid core optical fibres 58A, 58B58N to the input ends of an array of liquid core optical fibres 60A, 60B60N, each having an expansion chamber 62A, 62B62N.

The solid core fibres 58 act as launch fibres, as in the Figure 4 arrangement, and the two fibres connected to each coupler 56 are of different length, so that one fibre delays a signal from the coupler more than th 60 other.

The fourth port of each coupler 56 is connected by a solid core output optical fibre 64A, 64C64N to a detector 66. The detector 66 is connected through an amplifier 68 and a transient digitiser 70 to a microprocessor 72, which is connected to the laser 52 by trigger lines 74.

Each liquid core optical fibre 60 operates as in the Figure 4 arrangement. The microprocessor 72 operates 65 the lasers 52 to provide their input pulses to each coupler 56 at a different time. Each pulse is amplitude

divided in the coupler and the launch fibres 58 delay one divided pulse with respect to the other, so that each liquid core optical fibre 60A receives a laser pulse at a different time, and the detector 66 receives back-scattered light from each fibre 60 in turn without overlap.

In an alternative embodiment of a time-division multiplexed sensor as shown in Figure 6, a single pulsed laser 74 is connected to a star coupler 76 which supplies an array of solid core optical fibres 78A, 78C78N, all of different lengths to act as delay lines. Each fibre 78 is connected to one input of a four-port coupler 80A80N. Two outputs of each coupler 80 are connected to two further solid core optical fibres 82A, 82B82N, which act as launch fibres for an array of liquid core optical fibres 84A, 84B84N. The launch fibres are of different lengths to apply different delays to the pulse received by each coupler 80 as in Figure 5. The fibres 78 apply different delays to the laser pulse to provide a pulse to each coupler 80 at a different time.

The liquid core optical fibres illustrated in Figures 4, 5 and 6 may be of any suitable type. One possible construction is described in the specification of UK Patent No. 2,390,426.

Typically, a liquid core optical fibre consists of a hollow tube of silica or other glass drawn down to an external diameter of 300 micrometres and an internal diameter of 200 micrometres. If required, the interior or exterior of the tube may be modified before drawing by the deposition of a layer of material of a different refractive index to modify the optical or the mechanical properties of the fibre. For example a layer or layers of high-silica glass may be deposited inside the tube by, for example, chemical vapour deposition, so as to alter the refractive index of the glass in the vicinity of the core, thus modifying the waveguide properties, such as the numerical aperture, the number of modes guided, and the degrees to which the power is confined to the core. The attenuation of the cladding region may be similarly modified, and the attenuation of high-order modes or unbound modes of the core enhanced or reduced.

The outside of the tube may be coated with highly-attenuating layers to prevent the propagation of modes not bound to the core region.

During pulling, the tube may be coated, typically with polyimide or silicone, to improve the mechanical strength. Polyimide is optically opaque and therefore has the additional advantage of preventing spurious propagation in the silica cladding region.

After drawing, the tube is then filled with a suitable ultra-high-purity liquid. For example tetrachloroethylene or hexachlorobuta 1-3 diene may be used.

In any of the arrangements described with reference to Figures 4, 5 and 6, it is of course possible to replace the liquid core fibres by solid core fibres, when the solid core launch fibres will not be required.

In some cases it may be possible to use monomode fibres; in such fibres the scatter coefficient, varies with temperature, as in multimode fibres, but in addition the back-scattered power is sensitive to variations in the numerical aperture, because numerical aperture variations also cause changes in the back-scatter capture fraction S which can be detected.

Monomode fibres have an additional property which can be utilised in a distributed fibre optic sensor. In such fibres, a substantial proportion of the power is carried by the fibre cladding; the proportion depends strongly on the difference in the refractive indices of the core and the cladding, and if the index difference is temperature-sensitive, then the ratio of the powers carried by the core and the cladding also changes.

The index difference can be made sensitive to temperature by constructing the fibre so that the temperature coefficients of refractive index of the materials used for core and cladding differ markedly. Alternatively, by using core and cladding materials having very different thermal expansion coefficients, the core can be made highly stressed, being either in compression or tension, depending on whether the thermal expansion coefficient of the core is less or greater than that of the cladding. The induced stress in the core results in an increase or decrease in refractive index, which depends on the magnitude and sign of the stress optic coefficient. When the fibre is locally heated, the increase in temperature results in a reduction in thermal stress in the core and a consequent change in refractive index. The change in refractive index can be used to sense temperature variations.

If the cladding is made to have a high optical loss, such as by doping it with optically-absorbing ions, then the overall loss characteristic of the fibre will be temperature sensitive. In a further variation, if the scattering coefficients of the monomode fibre and its cladding are different, then the scatter return of the fibre will be temperature sensitive.

Another form of solid core optical fibre which may be used in the invention is a fibre in which the core and cladding materials have widely different temperature coefficients of refractive index, such as a glass and a plastic, as with a liquid core fibre, the numerical aperture of the fibre will then be highly temperature sensitive. In general, any combination of core/cladding materials can be used, including two different glasses, or two different plastics, provided that at least one optical property of the combination varies locally in accordance with the temperature.

As an alternative to sensing a change in an optical property of the fibre caused directly by temperature effects, a temperature sensing system according to the invention may include a bimetallic strip in mechanical contact with the fibre so as to induce a microbending loss which can be sensed by a back-scattering method. In further variations, a coating can be applied to an optical fibre which causes microbending loss of known form when the fibre is mechanically stressed; thus local pressure and stress changes could be sensed as well as temperature variations. A vibration sensor is also a possibility.

It is an advantage of the use of an optical fibre sensor according to the invention in which the

measurement is made optically that there are no hazards associated with electrical sparks if the equipment fails and that the sensor is immune to electromagnetic interference. The sensing equipment can be remote from the region of interest, and both temperature and position of any point along the fibre can be sensed.

5 CLAIMS


5

1. Detector apparatus including a fibre optic sensor comprising a length of optical fibre having a parameter which varies in accordance with a physical variable to be sensed, optical pulse supply means for supplying to said length of optical fibre a pulse of electromagnetic radiation at visible, ultraviolet or infrared wavelengths, radiation sensing means positioned to receive optical radiation back-scattered by the length of optical fibre and detector means responsive to said radiation sensing means to provide an output signal dependent on the intensity of the back-scattered radiation. 10
2. Detector apparatus as claimed in Claim 1 wherein said optical pulse supply means is a pulsed laser.
3. Detector apparatus as claimed in Claim 2 wherein said laser is a semiconductor laser.
4. Detector apparatus as claimed in Claim 3 wherein said semiconductor laser is adapted to emit radiation in the region of 0.85 to 0.91 micrometre wavelength. 15
5. Detector apparatus as claimed in Claim 1 or Claim 2 wherein said length of optical fibre has a liquid core.
6. Detector apparatus as claimed in Claim 5 wherein said liquid is trichlorethylene.
7. Detector apparatus as claimed in Claim 6 wherein said liquid is hexachlorobuta 1-3 diene. 20
8. Detector apparatus as claimed in any one of Claims 5 to 7, further including a launch fibre positioned between said optical pulse supply means and said length of optical fibre.
9. Detector apparatus as claimed in any one of the preceding claims wherein said length of optical fibre is at least partially immersed in a liquid.
10. A method of sensing the local value of a physical variable comprises providing a length of optical fibre having a parameter which responds to said physical variable, supplying to the fibre an optical pulse of radiation and sensing the variation of radiation back-scattered by said fibre. 25
11. Detector apparatus incorporating a length of optical fibre sensitive to changes in a physical variable substantially as herein described with reference to the accompanying drawings.

Printed for Her Majesty's Stationery Office, by Croydon Printing Company Limited, Croydon, Surrey, 1984.
Published by The Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.



DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 01 36916 A (SENSARRAY CORP) 25 May 2001 (2001-05-25)	1,8	G01M11/00
A	* page 6, line 5 - page 8, line 9; figures 1,12 *	2-7,9-12	
A	--- US 5 741 070 A (MOSLEHI MEHRDAD MAHMUD) 21 April 1998 (1998-04-21) * column 2, line 34 - column 2, line 45; claim 1; figure 4 *	1-12	
A	--- GB 2 122 337 A (NAT RES DEV) 11 January 1984 (1984-01-11) * page 1, line 25 - page 1, line 28 * * page 1, line 49 - page 2, line 4; figure 1 *	1-12	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G01M G01K
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 16 June 2003	Examiner Thomte, M
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	



**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 02 5300

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-06-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 0136916	A	25-05-2001	JP	2003515118 T	22-04-2003
			TW	455677 B	21-09-2001
			WO	0136916 A2	25-05-2001
<hr/>					
US 5741070	A	21-04-1998	US	5474381 A	12-12-1995
			CA	2136886 A1	31-05-1995
			DE	69428574 D1	15-11-2001
			DE	69428574 T2	27-06-2002
			EP	0655620 A1	31-05-1995
			JP	7311099 A	28-11-1995
<hr/>					
GB 2122337	A	11-01-1984	US	4714829 A	22-12-1987
<hr/>					

10